



CITY OF LODI

COMMUNITY DEVELOPMENT DEPARTMENT
Building Inspection Division
221 West Pine St/P.O. Box 3006, Lodi, CA 95241-1910
(209) 333-6714

STUCCO PERMIT APPLICATION

Jobsite Address _____

Project Description _____

Square footage of stucco area: _____

PROPERTY OWNER	PRIMARY NAME: <input type="checkbox"/>
Name: _____	
Address: _____	
City: _____	
State/Zip: _____	
Phone Number: _____	

CONTRACTOR	PRIMARY NAME: <input type="checkbox"/>
Name: _____	
License No: _____	Class: _____
Address: _____	
City/State/Zip: _____	
Phone Number: _____	
FAX Number: _____	
E-Mail: _____	

PROJECT MANAGER	PRIMARY NAME: <input type="checkbox"/>
Name: _____	
Phone 1: _____	
Phone 2: _____	
E-Mail: _____	
Address: _____	
City/State/Zip: _____	

Comments: _____

NOTICE: Applications for which no permit is issued within 180 days following the date of application shall expire by limitation, and plans and other data submitted for review may thereafter be returned to the applicant or destroyed by the building official.

APPLICANT SIGNATURE _____ Date _____

Application Accepted By _____ Date _____

NEW STUCCO APPLICATION FOR EXISTING BUILDINGS

Before you apply for a permit to stucco your existing building(s), please verify the following:

1. The building is structurally adequate. The walls are not leaning and the roof is not sagging.
2. The building should be anchored to an adequate foundation. For a single story building, the foundation should have a depth of 8 to 12 inches in undisturbed soil and 4 to 6 inches above grade with anchor bolts at 6 feet on center.
3. There should be adequate grade to wood clearance (six inches to ground or two inches to paved areas). See attached detail.

The inspector will verify all of these items on the first inspection. No refund will be processed once an inspection is conducted and the building is found to be substandard. If serious unsafe conditions are found and the application of stucco cannot be approved, the owner may be required to make the necessary corrections.

REQUIRED INSPECTIONS

1. Pre-inspection - Remove and replace all dry-rot and damaged wood. Remove all unsafe or exposed electrical wiring. Do NOT cover any existing exterior siding.
2. Lath (felt paper, wire and insulation board). 2 layers of grade D paper required when applied over wood base sheathing. DO NOT apply any stucco until the lath is approved.
3. Final – after all work is completed and all coats have been applied. All electrical fixtures and plumbing and mechanical vents shall be reinstalled.
4. Provide additional eave vents when using stucco to cove existing open overhang.

I hereby certify that I have read and understand the above requirements.

Property owner or authorized agent

Date

